

Chartpak, Inc.  
 One River Road  
 Leeds, MA 01053  
 Phone: 413-584-5446 or 800-628-1910

**Emergency Medical Number: 888-786-0972**

**Creation Date:** January 18, 2008

**Section One: Product Information**

Product Name: Max Grumbacher Artists' Oil Color  
 Product Sizes: 7.5, 24, 37, and 150 ml  
 Product Class: Artists' Oil Color

**Section Two: Ingredients**

Ingredients	CAS Number	% by Weight	PEL/TLV
Nickel Pigment	N/A	65.0%	N/A
Linseed Oil	8001-26-1	62.0%	N/A

**Section Three: Hazards Identification**

WARNING: EXPOSURE MAY CAUSE ALLERGIC REACTIONS.  
 CONTAINS: SOLUBLE NICKEL.  
 KEEP OUT OF REACH OF CHILDREN.  
 \*\*WARNING: This product contains a chemical known to the State of California to cause cancer.

**Section Four: First Aid Measures**

Inhalation: Move to fresh air.  
 Skin Contact: Wash with soap and water.  
 Eye Contact: Flush with flowing water.  
 Ingestion: Contact a physician. For further health information, contact a poison control center.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: M148

**Section Five: Fire Fighting Measures**

Flash Point: Not flammable

Flammability Limits (% by volume): Lower: Not explosive Upper: Not explosive

Extinguishing Media: As appropriate for surrounding area.

Special Fire Fighting Measures: No special fire fighting procedures.

Unusual Fire and Explosion Hazards: Not combustible

**Section Six: Accidental Release Measures**

No special spill procedures required

**Section Seven: Handling and Storage**

Handling: Wash hands immediately after use.

Storage: No special storage requirements.

**Section Eight: Exposure Controls and Personal Protection**

Respiratory Protection and Special Ventilation Requirements: None required

Other Protective Equipment (Gloves, Goggles, Etc.): Impervious protective gloves recommended.

Work/Hygiene Practices: PRECAUTIONS: Avoid prolonged contact with skin. Wash hands immediately after use. Not for use by children.

**Section Nine: Physical and Chemical Properties**

Boiling Point: Not determined Melting Point: Not determined

Vapor Pressure: Not determined Specific Gravity: Not determined

Specific Vapor Density (AIR = 1): Not determined Evaporation Rate (Butyl Acetate = 1): Not determined

Solubility in Water: Not determined Reactivity in Water: Non-reactive

Appearance and Odor: Colored paints; oily odor

**Section Ten: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: Excessive heat

Chemical Incompatibility: None known

Hazardous Decomposition: None known

Hazardous Polymerization: Will not occur

**Section Eleven: Toxicological Information**

IARC Monographs: No

National Toxicology Program: No

OSHA Regulated: No

Effects/Symptoms of Acute Exposure: Allergic reactions

Effects/Symptoms of Chronic Exposure: Allergic reactions

Medical Conditions Usually Aggravated By Overexposure of This Product: None known

**Section Twelve: Ecological Information**

Not available

**Section Thirteen: Disposal Considerations**

Dispose in accordance with Federal, State, and Local Regulations.

**Section Fourteen: Transport Information**

Not regulated as a hazardous material by DOT, IMO, or IATA.

**Section Fifteen: Regulatory Information**

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

**Section Sixteen: Other Information**

HMIS Code	
Health	1
Flammability	0
Reactivity	0
Personal Protection	N/A

Chartpak, Inc. is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the AP Seal. Products bearing the AP Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.

**0=Minimal / 4 = Severe**

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.